

RAMMER RSS15R SCRAP SHEAR



HYDRAULIC ROTATION WITH PROTECTION VALVE

The protected rotation system allows precision tool placement, lowering/reducing owning and operating costs.

BOLT ON, SYMMETRICAL CUTTER BLADES

Field replaceable and adjustable cutter blades minimize downtime and significantly increase the working life of wear parts

SMART JAWS DESIGN FEATURING DOUBLE GUIDE

Avoids material to stuck between the jaws which increases productivity and cutting capacity

SPEED VALVE

Shorter working cycles to increase productivity

HYDRAULIC CYLINDER SHIELDING

The cylinders are fully protected throughout the working cycle. Increasing durability and extending service intervals.

REPLACEABLE PEARCING TIP

A bolt on piercing tip, removes the need for welding and rebuilding which lowers the cost of owning and operation.

FIELD REPLACEABLE AND ADJUSTABLE CENTRAL PIN

Enables the operator to maintain the product on the site keeping cutting capacity on the maximum level.

RSS SCRAP SHEARS

The RSS Scrap Shears can be used in every industrial demolition job involving the cutting and recovery of ferrous materials such as iron sections, pipes, tanks, railway carriages etc

**Ram
mer**®

RSS15R

SPECIFICATIONS

Working weight, stick mounted, kg	1220
Working weight, boom mounted, kg	1320
Operating pressure, bar	250-300
Oil flow range, l/min	90-110
Rotation working pressure, bar	90-100
Rotation oil flow, l/min	30-40
Carrier weight stick mounted, ton	13-17
Carrier weight boom mounted, ton	8-12

